


A2F Type Single Compression Cable Gland

MM-EX-A2F-90 9N X6 (3.1/2" NPT)



CABLE GLAND SIZE DETAILS

Type	A2F Type Single Compression Cable Gland	CODE	MM-EX-A2F-90 9N X6 (3.1/2" NPT)
Cable Types	Unarmoured	CABLE GALND SIZE	90
Application	For indoor and outdoor use with all types of unarmoured cable where it is essential to provide IP66 or IP68 protection on the outer sheath of cable for circular, Unarmoured plastic or rubber sheathed cables.	ENTRT THREAD "C"	
Option thread	NPT	NPT	3 1/2"
Gland Material	Stainless Steel (SS316L)	THREAD LEGTH "E"	
IP Rating	IP66 & IP68	NPT	44
Gas Group	II C	CABLE DIAMETER "A"	
EPL (Equipment Protection Level)	Zone 1, Zone 2 Gb, Gc, Gas Zone 21, Zone 22, Db, Dc Dust	MIN	66.7
Sealing Ring	Single Compression Sealing	MAX	79.2
Operating Temperature	Silicone Seals: IECEx/ATEX-55°C ≤ Ta ≤ +160°C EAC-60°C ≤ Ta ≤ +130°C	HEX SIZE	
Finish	Natural Brass or Nickel Plated	M : MAX	108
Accessories	PVC Shroud, Lock Nut, Earth Tag, Serrated Washer, Adaptor / Reducer	N : MAX	116

IECEx Certificate No. ECEX PRE 20.0124X
ATEX Certificate No. Presafe 20 ATEX 48906X
EAC Certificate No. RU C-IN.AA71.B.00212/20
PESO Certificate No. P538496/4
Protection Type Ex d, Ex e, Ex t

- * Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)
- * All the dimensions given are in Millimeters (mm)
- * Can be also provided in Kit Packing as per requirement