

# Adaptor

## Metric to NPT



### MM-EX-AD3M5N B2 (M32 to 1 1/2"NPT)



#### Reducer

|                              |   |
|------------------------------|---|
| <b>IP Rating</b>             | IP68  |
| <b>IECEx Certificate No.</b> | IECEx PRE 20.0123X                                      |
| <b>ATEX Certificate No.</b>  | Presafe 20 ATEX 24571X                                  |
| <b>EAC Certificate No.</b>   | RU C-IN.AA71.B.00212/20                                 |
| <b>PESO Certificate No.</b>  | P538496/2   |
| <b>Thread Type</b>           | Metric to NPT   |
| <b>Protection Type</b>       | Ex d, Ex e, Ex t  |
| <b>Material</b>              | Brass Nickle Plated (BNP)                               |
| <b>Ambient Temperature</b>   | IECEx/ATEX-55°C ≤ Ta ≤ +160°C<br>EAC-60°C ≤ Ta ≤ +130°C |

#### Metric to NPT Thread

**CODE** MM-EX-AD3M5N B2 (M32 to 1 1/2"NPT)

|            |         |
|------------|---------|
| <b>A</b>   | M32X1.5 |
| <b>B</b>   | 1 1/2"  |
| <b>L</b>   | 43      |
| <b>A/F</b> | 16      |
| <b>G</b>   | 55      |

\* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)