

# Adaptor

## Metric to NPT



### MM-EX-AD6M6N B2 (M63 to 2"NPT)



#### Reducer

|                              |   |
|------------------------------|---|
| <b>IP Rating</b>             | IP68  |
| <b>IECEX Certificate No.</b> | IECEX PRE 20.0123X                                      |
| <b>ATEX Certificate No.</b>  | Presafe 20 ATEX 24571X                                  |
| <b>EAC Certificate No.</b>   | RU C-IN.AA71.B.00212/20                                 |
| <b>PESO Certificate No.</b>  | P538496/2   |
| <b>Thread Type</b>           | Metric to NPT   |
| <b>Protection Type</b>       | Ex d, Ex e, Ex t  |
| <b>Material</b>              | Brass Nickle Plated (BNP)                               |
| <b>Ambient Temperature</b>   | IECEX/ATEX-55°C ≤ Ta ≤ +160°C<br>EAC-60°C ≤ Ta ≤ +130°C |

#### Metric to NPT Thread

|             |                                |
|-------------|--------------------------------|
| <b>CODE</b> | MM-EX-AD6M6N B2 (M63 to 2"NPT) |
| <b>A</b>    | M63X1.5                        |
| <b>B</b>    | 2"                             |
| <b>L</b>    | 43                             |
| <b>A/F</b>  | 16                             |
| <b>G</b>    | 68                             |

\* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)