


Barrier Cable Gland - E1WB-BR Type

MM-EX-E1WB-20S 1N B2 (1/2")



Accessories

PVC Shroud
Lock Nut
Earth Tag
Serrated Washer
Seals
Adaptor / Reducer

BARRIER CABLE GLAND WITH FAST CURING LIQUID INJECTABLE EPOXY RESIN & SOLID EPOXY PUTTY

Effortless: Pronto Resin shall be injected with a hand-held gun and is easily applied with a mixing nozzle. Contrary to a sachet, liquid resins necessitate both hands for mixing.

COMPOUND

Barrier Compound's Available

1. Liquid Epoxy Resin

Gun



2. Solid Epoxy Putty



Double Compression Cable Gland For Armoured Cables

Type	E1WB Barrier Cable Gland
Cable Types	Suitable for Wire Braid Armour, STA, ASA, SWA, AWA, PWA, SWB armoured cables
Application	Gb (Zone 1 & 2), Gc (Zone 2) – Gas; Db (Zone 21 & 22), Dc (Zone 22) – Dust
Protection Type	Ex d, Ex e, Ex t

CABLE GLAND SIZE DETAILS

CODE	MM-EX-E1WB-20S 1N B2 (1/2")
CABLE GLAND SIZE	20s
Standard NPT Thread	1/2"
Optional NPT Thread	3/4"

Gas Group and Dust Group	IIC and IIIC	Thread Length C	16
EPL (Equipment Protection Level)	Gb (Zone 1 & Zone 2), GC (Zone 2) – Gas Db (Zone 21 & Zone 22), Dc (Zone 22) – Dust	Outer Sheath Min	10
Option Thread	NPT	Outer Sheath Max	12
Gland Material	Natural brass, naval grade brass	Inner Sheath Max Dia	9.6
IP Rating	IP66 and IP68 (5 meters, 10 Hrs)	Over Core Max Diab	15.5
Service Temperature Range	-40°C To +85°C	Max No. of Cores	12
IECEX Certificate No.	IECEX SGS 26.0002X	Armour Min	0.3
		Armour Max	1
ATEX Certificate No.	SGS26ATEX0010X	Orientation-1 Min	0.8
		Orientation-1 Max	1.25
		Across Flat	25
		Across Corners	27.5

* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)

* All the dimensions given are in Millimeters (mm)

* Can be also provided in Kit Packing as per requirement