


Barrier Cable Gland - E1WB-BR Type

MM-EX-E1WB-63 6M B2 (M63)



BARRIER CABLE GLAND WITH FAST CURING LIQUID INJECTABLE EPOXY RESIN & SOLID EPOXY PUTTY

Effortless: Pronto Resin shall be injected with a hand-held gun and is easily applied with a mixing nozzle. Contrary to a sachet, liquid resins necessitate both hands for mixing.

COMPOUND

Barrier Compound's Available

1. Liquid Epoxy Resin

Gun



2. Solid Epoxy Putty



Double Compression Cable Gland For Armoured Cables

Type	E1WB Barrier Cable Gland
Cable Types	Suitable for Wire Braid Armour, STA, ASA, SWA, AWA, PWA, SWB armoured cables
Application	Gb (Zone 1 & 2), Gc (Zone 2) – Gas; Db (Zone 21 & 22), Dc (Zone 22) – Dust
Protection Type	Ex d, Ex e, Ex t

CABLE GLAND SIZE DETAILS

CODE	MM-EX-E1WB-63 6M B2 (M63)
CABLE GLAND SIZE	63
Standard Metric Thread	M63×1.5
Optional Metric Thread	M75×1.5

Gas Group and Dust Group	IIC and IIIC	Thread Length C	16
EPL (Equipment Protection Level)	Gb (Zone 1 & Zone 2), GC (Zone 2) – Gas Db (Zone 21 & Zone 22), Dc (Zone 22) – Dust	Outer Sheath Min	51
		Outer Sheath Max	100
Option Thread	Metric	Inner Sheath Max Dia	54.6
Gland Material	Natural brass, naval grade brass	Over Core Max Diab	64.5
IP Rating	IP66 and IP68 (5 meters, 10 Hrs)	Max No. of Cores	100
Service Temperature Range	-40°C To +85°C	Armour Min	0.6
		Armour Max	1.6
IECEx Certificate No.	IECEx SGS 26.0002X	Orientation-1 Min	2
		Orientation-1 Max	2.5
ATEX Certificate No.	SGS26ATEX0010X	Across Flat	80
		Across Corners	89

* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)

* All the dimensions given are in Millimeters (mm)

* Can be also provided in Kit Packing as per requirement