

# Reducer

## Metric to Metric Thread



### MM-EX-RD2M1M B2 (M25 to M20)



#### Reducer

|                              |   |
|------------------------------|---|
| <b>IP Rating</b>             | IP68  |
| <b>IECEx Certificate No.</b> | IECEx PRE 20.0123X                                      |
| <b>ATEX Certificate No.</b>  | Presafe 20 ATEX 24571X                                  |
| <b>EAC Certificate No.</b>   | RU C-IN.AA71.B.00212/20                                 |
| <b>PESO Certificate No.</b>  | P538496/1   |
| <b>Thread Type</b>           | Metric to Metric  |
| <b>Protection Type</b>       | Ex d, Ex e, Ex t  |
| <b>Material</b>              | Brass Nickle Plated (BNP)                               |
| <b>Ambient Temperature</b>   | IECEx/ATEX-55°C ≤ Ta ≤ +160°C<br>EAC-60°C ≤ Ta ≤ +130°C |

#### Metric to Metric Thread

|             |                              |
|-------------|------------------------------|
| <b>CODE</b> | MM-EX-RD2M1M B2 (M25 to M20) |
| <b>A</b>    | M25X1.5                      |
| <b>B</b>    | M20X1.5                      |
| <b>L</b>    | 22                           |
| <b>A/F</b>  | 30                           |
| <b>G</b>    | 16                           |

\* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)