

# Reducer

## Metric to NPT Thread



### MM-EX-RD4M2N B2 (M40X1.5 to 3/4"NPT)



#### Reducer

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
| IP Rating             | IP68                                                    |
| IECEx Certificate No. | IECEx PRE 20.0123X                                      |
| ATEX Certificate No.  | Presafe 20 ATEX 24571X                                  |
| EAC Certificate No.   | RU C-IN.AA71.B.00212/20                                 |
| PESO Certificate No.  | P538496/2                                               |
| Thread Type           | Metric to NPT                                           |
| Protection Type       | Ex d, Ex e, Ex t                                        |
| Material              | Brass Nickle Plated (BNP)                               |
| Ambient Temperature   | IECEx/ATEX-55°C ≤ Ta ≤ +160°C<br>EAC-60°C ≤ Ta ≤ +130°C |

#### Metric to NPT Thread

**CODE** MM-EX-RD4M2N B2 (M40X1.5 to 3/4"NPT)

|            |         |
|------------|---------|
| <b>A</b>   | M40X1.5 |
| <b>B</b>   | 3/4"    |
| <b>L</b>   | 22      |
| <b>A/F</b> | 45      |
| <b>G</b>   | 16      |

\* Degrees of protection (IP Code) : IP66 / IP68 (1.5 meter, 2 Hours)